

Indoor Clocks

double face



Indoor
analog
double face

Type series
282



81.282.332 shown

Double face clocks for all places
where time must be readable
from either side. Robust metal,
fit everywhere!



Suffix -37

Metal cover for wall or ceiling mounting
brackets available as an option



71.282.333 -30

Clock case with lugs (option) for suspension by
metal ropes or chains

Case

- cir. 285x285 mm
- cir. 335x335 mm
- cir. 435x435 mm

very sturdy metal case, enamelled white (RAL 9016). Optionally, at a surcharge, the case may be enamelled in metallic silver grey (RAL 9006), in dark gun metal (DB 703) or custom enamelled, as listed below.

As an option, a stainless steel case (1.4301 X5CrNi 18-10, German trade name V2A) is available in a matted finish.

Protection grade IP 40 (EN 60 529).

Mounting

Choice of very sturdy wall or ceiling mounting brackets, standard length cir. 150 mm. For custom lengths or custom mounting options see table below.

Front glasses

Flat, shock-resistant Plexiglas® XT for outstandingly clear visibility.

Faces

High distinction white metal with black fine-line markings for easy, doubt-free reading even over longer distances.

Face printed according to DIN 41 091.

Hands

Black bar-type hour and minute hands, red second hands.

No second hands on DCF77 and AirPort24 radio controlled clocks and on minute pulse 12...60 V controlled slave clocks.

Double face clocks

Double face clocks come completely wired and pre-assembled. Just mount them and plug in – that's it!

Stainless steel V2A (option)

Due to its components stainless steel V2A is an alloy almost completely impervious to detergents and disinfectants and is therefore excellently suited for the use in the food and pharmaceutical industries, in kitchens, laboratories and other clean rooms. And it looks good into the bargain, as well!



Indoor analog double face

Type series

282



DCF77 radio controlled clocks

DCF77 radio controlled clocks of this type series will be supplied including a rotatable DCF77 aerial (IP 68). Thus, optimum reception quality can be achieved regardless of the final placement of the clock itself. However, DCF77 radio controlled clocks will only function correctly within a radius of approx. 1,500 km around Mainflingen (50 km east of Frankfurt/M.).

PEWETA DCFport24

PEWETA DCFport24 slave clocks require a PEWETA master clock (see from page 172 on).

PEWETA AirPort24

PEWETA AirPort24 slave clocks require an AirPort24 transmitter or repeater respectively (see page 177).

NTP

NTP system clocks require a PEWETA master clock (see from page 172 on) or an NTP time server (see page 179).

▼ Clock type	Face diameter ▶ Mounting ▼	250x250 mm		300x300 mm		400x400 mm	
		Item No.	€ each	Item No.	€ each	Item No.	€ each
DCF77 radio controlled clock, battery operated 1.5 V ¹⁾²⁾	wall	51.282.232	675.–	51.282.332	745.–	51.282.432	825.–
	ceiling	51.282.233	675.–	51.282.333	745.–	51.282.433	825.–
DCF77 radio controlled clock, mains operated 230 VAC ²⁾	wall	52.282.232	715.–	52.282.332	785.–	52.282.432	865.–
	ceiling	52.282.233	715.–	52.282.333	785.–	52.282.433	865.–
Slave clock, minute pulse 12...60 V	wall	71.282.232	419.–	71.282.332	459.–	71.282.432	539.–
	ceiling	71.282.233	419.–	71.282.333	459.–	71.282.433	539.–
Slave clock, minute/second pulse 12/24 V	wall	72.282.232	869.–	72.282.332	909.–	72.282.432	989.–
	ceiling	72.282.233	869.–	72.282.333	909.–	72.282.433	989.–
Slave clock, minute pulse 12/24 V, synchronous second hand 230 VAC/50 Hz	wall	74.282.232	1,239.–	74.282.332	1,279.–	74.282.432	1,359.–
	ceiling	74.282.233	1,239.–	74.282.333	1,279.–	74.282.433	1,359.–
Slave clock, second pulse 12/24 V, with creeping minute hand	wall	75.282.232	1,189.–	75.282.332	1,229.–	75.282.432	1,309.–
	ceiling	75.282.233	1,189.–	75.282.333	1,229.–	75.282.433	1,309.–
Telegram slave clock, DCFport24	wall	81.282.232	465.–	81.282.332	505.–	81.282.432	585.–
	ceiling	81.282.233	465.–	81.282.333	505.–	81.282.433	585.–
RC telegram slave clock, AirPort24, battery operated 1.5 V ¹⁾	wall	84.282.232	685.–	84.282.332	725.–	84.282.432	805.–
	ceiling	84.282.233	685.–	84.282.333	725.–	84.282.433	805.–
RC telegram slave clock, AirPort24, mains operated 230 VAC, with outage reserve	wall	85.282.232	725.–	85.282.332	765.–	85.282.432	845.–
	ceiling	85.282.233	725.–	85.282.333	765.–	85.282.433	845.–
NTP system clock (NTP client), synchronisation by LAN, PoE ³⁾	wall	91.282.232	635.–	91.282.332	675.–	91.282.432	755.–
	ceiling	91.282.233	635.–	91.282.333	675.–	91.282.433	755.–

Options	250x250mm Suffix	Surcharge € each	300x300mm Suffix	Surcharge € each	400x400mm Suffix	Surcharge € each
Case enamelled in metallic silver grey RAL 9006	-05	39.–	-05	45.–	-05	49.–
Case enamelled in metallic dark gun metal DB 703	-06	39.–	-06	45.–	-06	49.–
Case custom enamelled	-10	on request	-10	on request	-10	on request
Case stainless steel V2A, matted finish	-20	on request	-20	on request	-20	on request
Detachable ceiling mounting (length acc. to customer's choice)	-29	on request	-29	on request	-29	on request
Case with lugs for suspension by ropes or chains	-30	on request	-30	on request	-30	on request
Metal cover for wall or ceiling mounting brackets	-37	39.–	-37	39.–	-37	39.–
Stainless steel cover V2A for wall or ceiling mounting brackets	-38	95.–	-38	95.–	-38	95.–

Case colour	Suffix
■ metallic silver grey RAL 9006	-05
■ dark gun metal DB 703	-06
■ custom enamelled	-10
■ stainless steel V2A	-20

¹⁾ Alkaline batteries are included in delivery shipment (medium lifespan: cir. 4 years).

²⁾ A rotatable DCF77 receiving aerial is included in delivery shipment.

³⁾ NTP system clocks of "PoE" type require a PoE (Power over Ethernet) power supply. Appropriate hardware has to be supplied by customer.