

Clocks for Large Spaces

double-sided, indoor



Large space
analog
double-sided

Type series
352



71.352.512 shown



91.352.624

Large spaces call for large clocks!
Extremely sturdy clocks with **solid, industrial grade metal cases**.
Doubt-free reading of the exact time from afar – at any time.



81.352.513-06

Ceiling mount double bracket design and case enamelled in metallic dark gun metal (DB703) as an option



71.352.525

Case fitted with lugs for suspension by ropes or chains

Double-sided clocks
Double-sided clocks come completely wired and pre-assembled.
Just mount them and plug in – **that's it!**

Protection grade IP54 (option)
The IP protection grade defines the product's grade of protection against contact, foreign solid objects, and water.
The **first digit** indicates the degree of protection against solid foreign objects and contact:
5 = harmful amounts of dust deposits (Dust deposits are acceptable, but may not impede the product's function).
The **second digit** indicates the degree of protection against liquids and water respectively:
4 = Protection against water sprayed from all directions..

Case

- cir. 446 mm diameter
- cir. 546 mm diameter
- cir. 646 mm diameter

very sturdy metal case, enamelled metallic silver grey (RAL 9006) or, as an option, enamelled in dark gun metal (DB 703) or custom enamelled, as listed below. Protection grade IP 40 (EN 60 529).

Mounting

Choice of double bracket wall or ceiling mounting, standard bracket length cir. 210 mm, or sturdy metal tube suspension from the ceiling, tube length cir. 1000 mm. On request, custom length available optionally. Also available with lugs for suspension by ropes or chains.

Front glasses

Flat shock-resistant Plexiglas® XT (PMMA).

Packaging (option)

As an option, clockwork packaged to protect it against blown dust and/or sprayed water (IP 54 according to EN 60 529) is available.

Faces

High distinction white metal with large black Arabic numerals or black DIN bar markings for easy, doubt-free reading even over longer distances. Visible face diameter 420 mm, 520 mm and 620 mm respectively. Faces printed according to DIN 41 091.

Hands

Pointed black bar-type hour and minute hands according to DIN 41 092

Red second hands on slave clocks with minute/second pulse (72.xxx) and on slave clocks with synchronous second hands (74.xxx) only



Large space analog double-sided

Type series

352



DCF77 radio controlled clocks

DCF77 radio controlled clocks of this type series will be supplied including a remotable DCF77 aerial (IP 68). Thus, optimum reception quality can be achieved regardless of the final placement of the clock itself. However, DCF77 radio controlled clocks will only function correctly within a radius of approx. 1,500 km around Mainflingen (50 km east of Frankfurt/M.).

PEWETA DCFport24

PEWETA DCFport24 slave clocks require a PEWETA master clock (see from page 130 on).

PEWETA AirPort24

PEWETA AirPort24 slave clocks require an AirPort24 transmitter or repeater respectively (see page 135).

NTP

NTP system clocks require a PEWETA master clock (see from page 130 on) or an NTP time server (see page 137).

Clock type	Face diameter ▶	420 mm		520 mm		620 mm	
		Item No.	€ each	Item No.	€ each	Item No.	€ each
DCF77 radio controlled clock, battery operated 2x 1.5 V ¹⁾ 2)		51.352.	1,583.-	51.352.	1,737.-	51.352.	1,946.-
DCF77 radio controlled clock, mains operated 230 VAC ²⁾		52.352.	1,624.-	52.352.	1,778.-	52.352.	1,987.-
Slave clock, minute pulse 12...60 V		71.352.	1,225.-	71.352.	1,379.-	71.352.	1,583.-
Slave clock, minute/second pulse 12/24 V		72.352.	1,727.-	72.352.	1,881.-	72.352.	2,085.-
Slave clock, minute pulse 12/24 V, synchronous second hand 230 VAC/50 Hz		74.352.	2,065.-	74.352.	2,219.-	74.352.	2,423.-
Telegram slave clock, DCFport24, 24 V		81.352.	1,342.-	81.352.	1,496.-	81.352.	1,700.-
RC telegram slave clock, AirPort24, battery operated 2x 1,5 V ¹⁾		84.352.	1,590.-	84.352.	1,744.-	84.352.	1,948.-
RC telegram slave clock, AirPort24, mains operated 230 VAC		85.352.	1,631.-	85.352.	1,785.-	85.352.	1,989.-
NTP system clock (NTP client), synchronisation by LAN, PoE ³⁾		91.352.	1,578.-	91.352.	1,732.-	91.352.	1,936.-
Face print	Mounting	▲		▲		▲	
Arabic numerals	wall	412		512		612	
	ceiling	413		513		613	
	tube	414	+100.-	514	+100.-	614	+100.-
	lugs	415		515		615	
DIN bar markings	wall	422		522		622	
	ceiling	423		523		623	
	tube	424	+100.-	524	+100.-	624	+100.-
	lugs	425		525		625	
Options	420 mm Suffix	Surcharge € each	520 mm Suffix	Surcharge € each	620 mm Suffix	Surcharge € each	
Case enamelled in metallic dark gun metal DB 703	-06	none	-06	none	-06	none	
Case custom enamelled	-10	on request	-10	on request	-10	on request	
Custom length mounting fixture	-31	on request	-31	on request	-31	on request	
Packaging against dust and spray (IP 54)	-54	150.-	-54	150.-	-54	150.-	

Options – just as you like them ...

These clocks are available optionally with customised features at the surcharges as listed. Just pick your option(s) and add the appropriate suffix(es) to the Item No.

Case colour	Suffix
■ dark gun metal DB 703	-06
■ custom enamelled	-10

¹⁾ Alkaline batteries are included in delivery shipment (medium lifespan: cir. 4 years).

²⁾ A remotable DCF77 receiving aerial is included in delivery shipment.

³⁾ NTP system clocks of "PoE" type require a PoE (Power over Ethernet) power supply. Appropriate hardware has to be supplied by customer.